

# Introducing Our New 12GX Pure Lead Batteries



**POWER  
STORAGE  
SOLUTIONS**  
"Power is at the center of everything we do"



## Backed by our Full Five Year Warranty

### 12GX Pure Lead Series

| Model    | Battery Type | Description                                                                   | Length (mm) | Width (mm) | Height (mm) | Height Over Terminal (mm) | Wt Lbs (kg)    | Terminal | V  | Capacity @ 8 hr rate to 1.75VDC 77°F (25°C) |
|----------|--------------|-------------------------------------------------------------------------------|-------------|------------|-------------|---------------------------|----------------|----------|----|---------------------------------------------|
| 12GX40F  | Telecom      | 12V 38Ah @ 8 hr rate to 1.75 VDC, Front Term Pure Lead VRLA Battery, FR Case  | 11.76 (299) | 3.82 (97)  | 7.24 (184)  | 7.24 (184)                | 27.60 (12.5)   | M6       | 12 | 38                                          |
| 12GX100F | Telecom      | 12V 100Ah @ 8 hr rate to 1.75 VDC, Front Term Pure Lead VRLA Battery, FR Case | 15.96 (405) | 4.25 (108) | 11.29 (287) | 11.29 (287)               | 67.90 (30.8)   | M6       | 12 | 100                                         |
| 12GX190F | Telecom      | 12V 190Ah @ 8 hr rate to 1.75 VDC, Front Term Pure Lead VRLA Battery, FR Case | 22.01 (559) | 4.92 (125) | 12.60 (320) | 12.60 (320)               | 127.00 (57.6)  | M6       | 12 | 190                                         |
| 12GX210F | Telecom      | 12V 210Ah @ 8 hr rate to 1.75 VDC, Front Term VRLA Battery, FR Case           | 22.01 (559) | 4.92 (125) | 12.91 (328) | 12.91 (328)               | 135.80 (328.0) | M6       | 12 | 210                                         |

- Full five year warranty in standby applications
- Pure lead punched grids for consistent performance and lower float current for long life
- High energy density, fast charge acceptance
- Wide operating temperature range: -40°F to 149°F
- Low internal resistance with up to 2 year shelf life.
- Large top post & brass front terminal adapter
- Accessible gas port for air-tight enclosures
- UL Recognized, IEC Certified
- UL94V-0 flame retardant cases & covers
- 20 Year Design Life for Critical Telecom Applications

