





## **RB35-X**

Voltage: 12.8V | Capacity: 35 Ah | Energy: 448 Wh | Group: U1

LITHIUM IRON PHOSPHATE BATTERY LifePO4

ELECTRICAL SPECIFICATIONS		
Nominal Voltage	12.8 V	
Nominal Capacity	35 Ah	
Capacity @ 25A	84 min	
Resistance	≤50 mΩ @ 50% SOC	
Efficiency	99%	
Self Discharge	<3% per Month	
Maximum Modules in Series	1	

DISCHARGE SPECIFICATIONS	
Maximum Continous Discharge Current	70 A
Peak Discharge Current	100 A (7.5 s ±2.5 s)
BMS Discharge Current Cut-Off	160 A ±20 A (9 ±4 ms)
Recommended Low Voltage Disconnect	11 V
BMS Discharge Voltage Cut-Off	8 V (2.0 ±0.08 vpc) (144 ±30 ms)
Reconnect Voltage	8.64 V ±0.96 V (2.16 ±0.24 vpc)
Short Circuit Protection	200-800 μs


TEMPERATURE SPECIFICATIONS		
Discharge Temperature	-4 to 140 °F (-20 to 60 °C)	
Charge Temperature*	-4 to 113 °F (-20 to 45 °C)	
Storage Temperature	14 to 95 °F (-10 to 35 °C)	
BMS High Temperature Cut-Off	167 °F (75 °C)	
Reconnect Temperature	122 °F (50 °C)	

<sup>\*</sup>Refer to charge currents below 32°F (0°C)

MECHANICAL SPECIFICATIONS		
Dimensions (L x W x H)	7.7 x 5.2 x 6.7" 195 x 131 x 171 mm	
Weight	11.4 lbs (5.17 kg)	
Terminal Type	M8 x 1.25 x 12mm	
Terminal Torque	80 - 100 in-lbs (9 - 11 N-m)	
Case Material	ABS	
Enclosure Protection	IP66	
Cell Type - Chemistry	Cylindrical - LiFePO <sub>4</sub>	

CHARGE SPECIFICATIONS		
Recommended Charge Current	1.75 A - 17.5 A	
Maximum Charge Current	70 A	
Charge Current 14 to 32 °F (-10 to 0 °C)	≤0.1 C	
Charge Current -4 to 14 °F (-20 to -10 °C)	≤0.05 C	
Recommended Charge Voltage	14.2 V - 14.6 V	
BMS Charge Voltage Cut-Off	15.6 V (3.9 ±0.025 vpc) (1.2 ±0.3 s)	
Reconnect Voltage	15.2 V (3.8 ±0.050 vpc)	
Balancing Voltage	14.4 V (3.6 ±0.025 vpc)	

COMPLIANCE SPECIFICATIONS	
Certifications	CE (battery) UL1642 (cells) (File# MH62098) IEC62133 (cells)
Shipping Classification	UN 3480, CLASS 9









## **RB35-X**

Voltage: 12.8V | Capacity: 35 Ah | Energy: 448 Wh | Group: U1

LITHIUM IRON PHOSPHATE BATTERY LIFEPO4

